



WITH 80' - 102' R.O.W.
PARALLEL OR 30° ANGLED PARKING
NTS

GENERAL NOTES:

- PAVEMENT SECTION IN
 ACCORDANCE WITH STANDARD
 DRAWING OR APPROVED PAVEMENT
 DESIGN PER PS-01.
- 2. ALL WORK IN PUBLIC RIGHT-OF-WAY SHALL BE CONSTRUCTED BY A LICENSED CONTRACTOR AND REQUIRES A PERMIT AND APPROVAL BY THE DEPT. OF PUBLIC WORKS.

KEYED NOTES:

- 1 6" SPILL C&G. SEE DWG. CG-01
- 2 4" THICK CONCRETE SIDEWALK. SEE DWG. DW-01. AN ASPHALT PATH MAY BE SUBSTITUTED FOR SIDEWALK ON ONE SIDE OF THE ROAD WITH CITY ENGINEER'S APPROVAL. THE PATH MUST BE A MINIMUM OF 8' WIDE.
- (3) INVERTED CROWN VALLEY GUTTER. SEE DWG VG-01

(4) LANDSCAPING AND OTHER AMMENITIES MAY BE PLACED IN THE SIDEWALK AREA, BUT MAY NOT INFRINGE UPON A CLEAR PATH OF 8' WIDE.



City of Rio Rancho Department of Public Works

TYPICAL STREET SECTION
BUSINESS COLLECTOR
PARALLEL / 30° ANGLED PARKING

DWG. NO. TS-03

SEPT 23, 2008